

borg &
overström



Beautifully
refreshing.

u2

borg&
overström

High-performance hydration

Practical, reliable and visually striking, this innovative tap brings a high capacity refreshment solution to any commercial or Horeca environment.

Reasons to choose

- High capacity output
- Low energy consumption
- Compact under-counter unit
- Robust, solid build quality
- Simple to operate and maintain
- Drip tray and ventilation kit included

borgandoverstrom.com



Beautifully
refreshing.

u2

Water system



Direct Chill

Configuration



Undercounter

Water options



Chilled



Ambient



11-25



25+



Sparkling



Beautifully
refreshing.

Catering for capacity

The U2 boasts a compact yet high capacity under-counter appliance. It delivers a speedy throughput of 40 litres per hour at a consistent chilled temperature, making it the perfect solution for busy environments including Horeca applications.

Borg & Overström Totality™



Driven by a relentless pursuit of excellence, Borg & Overström Totality™ is a research and development methodology for the advancement of hygiene, innovation and technology in refreshment systems.



Ultra-violet sterilising system
For added hygiene confidence, appliances can be fitted with Viovand™ – an ultra-violet sterilisation process that reduces water-borne bacteria.



Laboratory certified 99.999% bacteria-free
Every Borg & Overström appliance undergoes an anti-microbial, antipathogen, sanitising procedure. The reassurance of hygienically safe appliances is provided by the unique bacteria-eliminating process, Sterizen™.



World-class filtration
For the ultimate drinking experience, Borg & Overström appliances can be pre-fitted with a 3M filter to reduce sediment, chlorine, odours and scale.

Beautifully refreshing.

U2 Models

Direct Chill

Chilled, Sparkling	601512
Chilled, Ambient & Sparkling	601513

Dimensions	WxDxH
Undercounter - 40L	330x370x362mm
Twin Head Tap	150x240x470mm
Dispense height	250mm
Max power consumption	
Chilled & Sparkling 300W	

Power requirements
Hertz 50/Volts 230
Chilled temperature
Min 1°C/Max 12°C
Throughput litres per hour
Chilled 40

Dimensions	WxDxH
Undercounter - 40L	330x370x362mm
Triple Head Tap	215x240x470mm
Dispense height	285mm
Max power consumption	
Chilled, Ambient & Sparkling 300W	

Beautifully
refreshing.

Additions for U2



Printed paper cups

Environmentally-friendly disposable cups designed to fit Borg & Overström cup dispensers perfectly.



750ml glass bottles

Suitable for dishwashers and bottlewashers. Perfect fit for the U2 tap. Stylish swing-top lid.



Deep-sparkle CO² refills

Can be disposed via standard steel recycling or general waste. Requires CO² regulator with gauge.



Sanitisation kit

Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



Waste kit overflow sensor

Featuring an audible high-water level alarm to prevent the waste tank from overflowing.



Freestanding drip tray

Alternative non-plumbed drip tray for where integrated drip trays cannot be used.



Install kit with 3M filter

Install appliances simply and effectively in a wide range of applications. Complete with a 3M filter.



Ultra-violet filter kit

Complete Viovandt™ filter kit to assist in water purification and removal of unwanted micro-organisms.

Beautifully
refreshing.

borg&
overström

Book a visit to the Borg & Overström Academy
for a personal demonstration of the new U2

Talk to an adviser
+44 (0) 1362 695 006
sales@borgandoverstrom.com