

HydroTap

Industrial.

In settings where safety, security, and durability are top of the agenda, look no further than the HydroTap Industrial. Designed specifically for ease of use and robustness, the HydroTap Industrial is made to last, even in the most demanding environments. Reliably delivering instant filtered boiling and chilled water, it has easy to use controls and unique safety features. Commercial models only.

Boiling & Chilled









Designed to withstand rigorous use in industrial environments


The tap features a safety lock to deliver boiling water

Optional additional parts allow the tap to be installed on a worktop or away from a sink



HydroTap

Industrial.



Available in a beautiful and durable Bright Chrome Finish.

BRIGHT CHROME



Technical Specifications

Water functions	Boiling and Chilled
Finish	Bright Chrome
Product weight - empty / full	28kg / 33kg
Boiling capacity	Dependent on Model*
Chilled capacity	Dependent on Model*
Water temperature	Boiling 98°C Chilled 3-5°C
Installation hole cut size	35mm
Supply pressure range	1.7bar - 5bar
Power supply requirements	1 x 13amp socket outlet
Voltage supply	13 amps
Power rating	2.13 kW @ 230V
Supply connection	1 x isolated 1/2"bsp BSP fitting (flexible supply hoses included)
Filtration	0.2 Micron Filter Cartridge
Flow rate	3.0-4.0 l/min
Refrigerant	R134a
Tank material	Stainless Steel
Command Centre	Clearance space required for under counter unit
Command Centre Dimensions (W x D x H)	450mm x 470mm x 335mm

^{*}Boiling and Chilled capacity is dependant on the Model, ranging between 160 cups per hour, up to 240 cups per hour. Please contact us to discuss your options.

We supply a wide range of commercial and residential models. Please get in touch to tell us what you are looking for.

